

(Nanocommunications) Short Pulse Time Domain Modulation Techniques (OOK-TS Keying Off-On)

Dr.Afshin Rashid , Assistant Professor

Faculty member Islamic Azad University of Science and Research Branch, Tehran

- **Abstract:**

- Noise is a low-frequency random oscillation that occurs in many nanocommunication devices, including nanoelectronics, the environment, and organisms. Noise can obscure signals, so it is often omitted from electronic and radio transmissions. The origin of noise in nanoelectronics is currently mostly in carbon nanotubes based on the nanocommunicative functions and the structure of graphene particles in nanotubes in interaction for nanocommunication purposes by (nanoparticles) in single-walled carbon nanotubes (SWCNTs) and multi-walled CNTs.

- **Keywords:** Nanocommunications , terahertz , electromagnetic waves , nanoantenna

Introduction •

Nanomaterials with high surface-to-volume ratio of noise generated by nanoelectrons are very attractive because they are very sensitive to changes in their surface. A representative material of this type is carbon nanotubes, which are rolled sheets of hexagonal graphene lattice, which are only one carbon atom thick. In nanocommunications, different molecules give off unique acoustic signals related to the properties of the molecules. The strength of the interaction between carbon nanotubes and the molecules arises from the noise signals. In nanocommunications, the signal generated by the carbon nanotube-based electronic nanoparticles is modified following the absorption of specific single molecules. This is because

the absorbing molecule creates a trap state in the carbon nanotube, which causes it to conduct. This means that carbon nanotube-based nanocommunications devices are very sensitive. They can detect an unprecedented amount of single molecules. The ability to characterize single molecules using highly sensitive nanoelectronics is an exciting prospect in the field of sensors, especially for neurosensory and biosensor applications. The use of acoustic signals to detect molecular activity ((interaction) or (active orbital)) is attractive. In nanocommunications and interaction with carbon nanotube-based electronic nanoparticles, the sensitivity of signal detection may be increased by the generation of controllable noise. These carbon nanotube-based nanocommunicators demonstrate the possibility of identifying individual molecules through their unique noise particles in current nanocommunicator signals. Improved knowledge of the molecular origin and interaction of nanoparticle-based carbon nanotube-based electronic noise should lead to the development of electronics that use noise to improve their performance rather than degrade it.

(Nanocommunications) Short Pulse Time Domain Modulation Techniques (OOK-TS: Keying Off-On)

Classical communication models based on continuous signal communication cannot be implemented, and for WSNs, short time-domain keying (OOK-TS: Keying Off-On) pulse modulation techniques are used. Therefore, these techniques are especially used in cases such as frequency detection systems as well as the nano-Internet of Things. Waves as information carriers similar to classical communications. However, due to the severe resource shortage and quantum effects of materials, classical methods cannot be directly applied to the nano-domain. Hence, it is necessary to use new materials and techniques. Nanodevices communicate at frequencies of about 1.0 to 10 terahertz. Due to the severe limitations of nanodevices in terms of size and energy, generating high-power signals at terahertz frequencies is not practical. In a molecular communication system, the transmitter sends information by chemical molecules called information molecules, and after being propagated in the environment, it is received and decoded by the communication receiver. Communication theories play a special role in modeling, analyzing, and designing molecular communication systems. Nano-network is a nano-scale communication network between nano-devices. Nano-devices face special challenges in performance due to limitations in processing power management capabilities. Hence, these devices are expected to perform simple tasks that require different and novel approaches. In nano-communication, different molecules give off unique acoustic signals related to the properties of the molecules. There are several nano-communication technologies that require the use of external excitation and measurement to work. Wireless communication between nano-networks and micro- and macro-devices and equipment can meet this need. Molecular communication is the sending and receiving of information encoded in molecules, while electromagnetic communication is the sending and receiving of electromagnetic radiation from different nano-devices. Of these methods, molecular communication and electromagnetic communication are wireless methods.

References :

Mohamadi, P., G. R. Dadashzadeh, and M. Naser-Moghadasi. "A new symmetric multimodal MIMO antenna with reduction of modal correlation coefficient using TCM." *IETE Journal of Research* 66.2 (2020): 150-159, <http://dx.doi.org/HYPERLINK>

["http://dx.doi.org/10.1080/03772063.2018.1481460"](http://dx.doi.org/10.1080/03772063.2018.1481460) HYPERLINK
["http://dx.doi.org/10.1080/03772063.2018.1481460/"](http://dx.doi.org/10.1080/03772063.2018.1481460/) HYPERLINK
["http://dx.doi.org/10.1080/03772063.2018.1481460"](http://dx.doi.org/10.1080/03772063.2018.1481460)03772063.2018.1481460

Bakhtiari A, Sadeghzadeh RA, Naser-Moghaddasi M. Millimeter-wave beam-steering high gain array antenna by utilizing metamaterial zeroth-order resonance elements and Fabry-Perot technique. International Journal of Microwave and Wireless Technologies. 2018;10(3):376-382.

<http://> HYPERLINK ["http://dx.doi.org/10.1017/S1759078717001301"](http://dx.doi.org/10.1017/S1759078717001301)dx. HYPERLINK
["http://dx.doi.org/10.1017/S1759078717001301"](http://dx.doi.org/10.1017/S1759078717001301)doi. HYPERLINK
["http://dx.doi.org/10.1017/S1759078717001301"](http://dx.doi.org/10.1017/S1759078717001301)org/ HYPERLINK
["http://dx.doi.org/10.1017/S1759078717001301"](http://dx.doi.org/10.1017/S1759078717001301)10.1017 HYPERLINK
["http://dx.doi.org/10.1017/S1759078717001301/"](http://dx.doi.org/10.1017/S1759078717001301/) HYPERLINK
["http://dx.doi.org/10.1017/S1759078717001301"](http://dx.doi.org/10.1017/S1759078717001301)S HYPERLINK
["http://dx.doi.org/10.1017/S1759078717001301"](http://dx.doi.org/10.1017/S1759078717001301)1759078717001301

Vahedian, M., Naser-Moghaddasi, M. The nano loop antenna with Fano resonance and symmetrical formation and reconfigurable characteristic for bio-sensing application. Opt Quant Electron 50, 178 (2018). [https://](https://doi.org/10.1007/s11082-018-1449-5) HYPERLINK ["https://doi.org/10.1007/s11082-018-1449-5"](https://doi.org/10.1007/s11082-018-1449-5)doi.

HYPERLINK ["https://doi.org/10.1007/s11082-018-1449-5"](https://doi.org/10.1007/s11082-018-1449-5)org/ HYPERLINK
["https://doi.org/10.1007/s11082-018-1449-5"](https://doi.org/10.1007/s11082-018-1449-5)10.1007 HYPERLINK
["https://doi.org/10.1007/s11082-018-1449-5/"](https://doi.org/10.1007/s11082-018-1449-5/) HYPERLINK ["https://doi.org/10.1007/s11082-018-1449-5"](https://doi.org/10.1007/s11082-018-1449-5)s HYPERLINK ["https://doi.org/10.1007/s11082-018-1449-5"](https://doi.org/10.1007/s11082-018-1449-5)11082-018-1449-5

Bakhtiari, A., Sadeghzadeh, R. A., & Moghaddasi, M. Naser. (2018). Gain Enhanced Miniaturized Microstrip Patch Antenna Using Metamaterial Superstrates. IETE Journal of Research, 65(5), 635–640. [https://](https://doi.org/10.1080/03772063.2018.1447406) HYPERLINK

["https://doi.org/10.1080/03772063.2018.1447406"](https://doi.org/10.1080/03772063.2018.1447406)doi. HYPERLINK
["https://doi.org/10.1080/03772063.2018.1447406"](https://doi.org/10.1080/03772063.2018.1447406)org/ HYPERLINK
["https://doi.org/10.1080/03772063.2018.1447406"](https://doi.org/10.1080/03772063.2018.1447406)10.1080 HYPERLINK
["https://doi.org/10.1080/03772063.2018.1447406/"](https://doi.org/10.1080/03772063.2018.1447406/) HYPERLINK
["https://doi.org/10.1080/03772063.2018.1447406"](https://doi.org/10.1080/03772063.2018.1447406)03772063.2018.1447406

Shohreh Nouri-Novin, Ferdows B. Zarrabi, Ahmad-Reza Eskandari, Mohammad Naser-Moghaddasi, Design of a plasmonic absorber based on the nonlinear arrangement of nanodisk for surface cloak, Optics Communications, Volume 420, 2018, Pages 194-199, ISSN 0030-4018,

[https://](https://doi.org/10.1016/j.optcom.2018.03.064) HYPERLINK ["https://doi.org/10.1016/j.optcom.2018.03.064"](https://doi.org/10.1016/j.optcom.2018.03.064)doi. HYPERLINK
["https://doi.org/10.1016/j.optcom.2018.03.064"](https://doi.org/10.1016/j.optcom.2018.03.064)org/ HYPERLINK
["https://doi.org/10.1016/j.optcom.2018.03.064"](https://doi.org/10.1016/j.optcom.2018.03.064)10.1016 HYPERLINK
["https://doi.org/10.1016/j.optcom.2018.03.064/"](https://doi.org/10.1016/j.optcom.2018.03.064/) HYPERLINK
["https://doi.org/10.1016/j.optcom.2018.03.064"](https://doi.org/10.1016/j.optcom.2018.03.064)j. HYPERLINK
["https://doi.org/10.1016/j.optcom.2018.03.064"](https://doi.org/10.1016/j.optcom.2018.03.064)optcom. HYPERLINK
["https://doi.org/10.1016/j.optcom.2018.03.064"](https://doi.org/10.1016/j.optcom.2018.03.064)2018.03.064

High-gain, high-isolation, and wideband millimetre-wave closely spaced multiple-input multiple-output antenna with metamaterial wall and metamaterial superstrate for 5G applications. (2021).

IET Microwaves, Antennas Propagation, 15 (4). [https://](https://doi.org/10.1049/mia2.12055D) HYPERLINK
["https://doi.org/10.1049/mia2.12055D"](https://doi.org/10.1049/mia2.12055D)doi. HYPERLINK

["https://doi.org/10.1049/mia2.12055D"org/](https://doi.org/10.1049/mia2.12055D) HYPERLINK
["https://doi.org/10.1049/mia2.12055D"10.1049](https://doi.org/10.1049/mia2.12055D) HYPERLINK
["https://doi.org/10.1049/mia2.12055D"/](https://doi.org/10.1049/mia2.12055D/) HYPERLINK
["https://doi.org/10.1049/mia2.12055D"mia](https://doi.org/10.1049/mia2.12055D) HYPERLINK
["https://doi.org/10.1049/mia2.12055D"2.12055](https://doi.org/10.1049/mia2.12055D) HYPERLINK
["https://doi.org/10.1049/mia2.12055D"D](https://doi.org/10.1049/mia2.12055D)

Design and Analysis of a New Wide-Band Epsilon Negative Metamaterial for X-Band Applications. (2020).IETE Journal of Research,68 (6). [https://](https://doi.org/10.1080/03772063.2020.1792357) HYPERLINK
["https://doi.org/10.1080/03772063.2020.1792357"doi.](https://doi.org/10.1080/03772063.2020.1792357) HYPERLINK
["https://doi.org/10.1080/03772063.2020.1792357"org/](https://doi.org/10.1080/03772063.2020.1792357) HYPERLINK
["https://doi.org/10.1080/03772063.2020.1792357"10.1080](https://doi.org/10.1080/03772063.2020.1792357) HYPERLINK
["https://doi.org/10.1080/03772063.2020.1792357"/](https://doi.org/10.1080/03772063.2020.1792357/) HYPERLINK
["https://doi.org/10.1080/03772063.2020.1792357"03772063.2020.1792357](https://doi.org/10.1080/03772063.2020.1792357)

Design of Branch Line Coupler based on Ridge Gap Waveguide Technology for X-band Application. (2019).IETE Journal of Research,68 (2). [https://](https://doi.org/10.1080/03772063.2019.1627916) HYPERLINK
["https://doi.org/10.1080/03772063.2019.1627916"doi.](https://doi.org/10.1080/03772063.2019.1627916) HYPERLINK
["https://doi.org/10.1080/03772063.2019.1627916"org/](https://doi.org/10.1080/03772063.2019.1627916) HYPERLINK
["https://doi.org/10.1080/03772063.2019.1627916"10.1080](https://doi.org/10.1080/03772063.2019.1627916) HYPERLINK
["https://doi.org/10.1080/03772063.2019.1627916"/](https://doi.org/10.1080/03772063.2019.1627916/) HYPERLINK
["https://doi.org/10.1080/03772063.2019.1627916"03772063.2019.1627916](https://doi.org/10.1080/03772063.2019.1627916)

A New Symmetric Multimodal MIMO Antenna with Reduction of Modal Correlation Coefficient Using TCM.(2018). IETE Journal of Research,66 (2). [https://](https://doi.org/10.1080/03772063.2018.1481460) HYPERLINK
["https://doi.org/10.1080/03772063.2018.1481460"doi.](https://doi.org/10.1080/03772063.2018.1481460) HYPERLINK
["https://doi.org/10.1080/03772063.2018.1481460"org/](https://doi.org/10.1080/03772063.2018.1481460) HYPERLINK
["https://doi.org/10.1080/03772063.2018.1481460"10.1080](https://doi.org/10.1080/03772063.2018.1481460) HYPERLINK
["https://doi.org/10.1080/03772063.2018.1481460"/](https://doi.org/10.1080/03772063.2018.1481460/) HYPERLINK
["https://doi.org/10.1080/03772063.2018.1481460"03772063.2018.1481460](https://doi.org/10.1080/03772063.2018.1481460)

Quasi-self-complementary planar broadband series-fed array antenna for C-band applications. (2016). Mi-crowave and Optical Technology Letters,59(1). [https://](https://doi.org/10.1002/mop.30228) HYPERLINK
["https://doi.org/10.1002/mop.30228"doi.](https://doi.org/10.1002/mop.30228) HYPERLINK ["https://doi.org/10.1002/mop.30228"org/](https://doi.org/10.1002/mop.30228) HYPERLINK
["https://doi.org/10.1002/mop.30228"10.1002](https://doi.org/10.1002/mop.30228) HYPERLINK
["https://doi.org/10.1002/mop.30228"/](https://doi.org/10.1002/mop.30228/) HYPERLINK ["https://doi.org/10.1002/mop.30228"mop.](https://doi.org/10.1002/mop.30228) HYPERLINK
["https://doi.org/10.1002/mop.30228"30228](https://doi.org/10.1002/mop.30228)

Alibakhshikenari, M., Virdee, B.S., Benetatos, H., Ali, E.M., Soruri, M., Dalarsson, M., Naser-Moghadasi, M., See, C.H., Pietrenko-Dabrowska, A., Koziel, S. and Szczepanski, S., 2022. An innovative antenna array with high inter element isolation for sub-6 GHz 5G MIMO communication systems. Scientific Reports, 12(1), p.7907 [http://](http://dx.doi.org/10.1038/s41598-022-12119-2) HYPERLINK
["http://dx.doi.org/10.1038/s41598-022-12119-2"dx.](http://dx.doi.org/10.1038/s41598-022-12119-2) HYPERLINK
["http://dx.doi.org/10.1038/s41598-022-12119-2"doi.](http://dx.doi.org/10.1038/s41598-022-12119-2) HYPERLINK
["http://dx.doi.org/10.1038/s41598-022-12119-2"org/](http://dx.doi.org/10.1038/s41598-022-12119-2) HYPERLINK
["http://dx.doi.org/10.1038/s41598-022-12119-2"10.1038](http://dx.doi.org/10.1038/s41598-022-12119-2) HYPERLINK
["http://dx.doi.org/10.1038/s41598-022-12119-2"/](http://dx.doi.org/10.1038/s41598-022-12119-2/) HYPERLINK

["http://dx.doi.org/10.1038/s41598-022-12119-2"s HYPERLINK](http://dx.doi.org/10.1038/s41598-022-12119-2)
["http://dx.doi.org/10.1038/s41598-022-12119-2"41598-022-12119-2](http://dx.doi.org/10.1038/s41598-022-12119-2)